

77205D-LPV-PS Turn-n-Wrap Low Profile semi-automatic stretch wrapper with 200% Powered pre-stretch

OVERVIEW

If your looking for a heavy-duty, high volume, low maintenance stretch wrapper the Powered pre-stretch D series is the answer. With this easy to operate machine you load the 58" variable speed turntable, attach the wrap to the load, hit the switch and walk away. The carriage raises and wraps the load until the photo electric eye senses the top of the load. When the top of the load is sensed a preset number of wraps are applied. After the number of wraps the film carriage then reverses itself and continues to wrap the load as it lowers. When it reaches the bottom, the turntable stops in the same position that it started for easy unloading. These machines with their 200% fixed Powered pre-stretch dispenser will pre-stretch your film to the load adding minimal force to light loads and obtain higher film yield.

SPECIFICATIONS

Maximum Load Size:	56" x 56" x 76"
Production Capacity:	40 loads per hour
Machine Dimensions:	111"L x 58"W x 83"H
Weight Capacity:	5,000 LB.
Electrical Data:	120 VAC 60 Hertz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	58" Round Steel Diamond Deck
Turntable Height:	3 5/8"
Turntable Drive:	3/4 hp DC Motor (Totally Enclosed Fan Cooled) Variable Speed Turntable 0-15 RPM with Soft Start and Soft Stop 4 Point Cam Follower Turntable Supports Easy Access Lubrication Points on Turntable Heavy-Duty #50 Roller Chain & Drive Sprocket Synthetic Lube in all Gearboxes (-30 - 120°F) Turntable Indexing Home Alignment
Controls:	Power On / Off with Indicator Manual / Semi-Auto Switch Turntable Variable Speed Dial Dispenser Variable Speed Dial Film tension Variable Dial Film Carriage Up / Down Switch Emergency Stop Button 9 Diagnostic Lights for easy trouble shooting Photo Eye for Automatic Load Height Sensing Adjustable Top Wraps Adjustable Top of Load Over Wrap Turntable Indexing Home Alignment



Shown with optional scale

Film Delivery:	Powered Pre-Stretch Stretch Level 200% fixed (gear switch to 250% or 300%) Force to Load dial for different load weights Accepts 12"-20" Rolls of Stretch Film 1/2 hp DC 90 Volt Motor
Film Carriage:	74" Wrap Height (Optional Wrap Height Available) Top Over Wrap Variable Speed Carriage 0-20 FPM 1/4 hp 90 Volt DC Motor 12 Point UHMW Carriage Guide Supports Dispenser Kill Switch Top / Bottom
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Easy Access to all Components Forklift Portable from Front and Rear
Warranty:	3 year limited warranty
Shipping Weight:	1,125 lb.