


77205D-LPV Turn-n-Wrap low profile semi-automatic stretch wrapper with Electro mechanical brake-motor film dispenser

OVERVIEW

If your looking for a heavy-duty, high volume, low maintenance stretch wrapper the D series is the answer. With this easy to operate machine you load the 58" variable speed turntable, attach the wrap to the load, hit the switch and walk away. The carriage raises and wraps the load until the photo electric eye senses the top of the load. When the top of the load is sensed a preset number of wraps are applied. After the number of wraps the film carriage then reverses itself and continues to wrap the load as it lowers. When it reaches the bottom, the turntable stops in the same position that it started for easy unloading. These machines with their 30%-250% Powered Brake motor stretch dispenser will save material, increase worker productivity and offer the best value for a semi-automatic wrapper.

SPECIFICATIONS

Maximum Load Size:	56" x 56" x 76"
Production Capacity:	40 loads per hour
Machine Dimensions:	85"L x 48"W x 83"H
Weight Capacity:	5,000 LB.
Electrical Data:	120 VAC 60 Hertz 20 Amps. Conventional style 3 prong power cord. UL approved components.
Turntable Size:	58" Round Steel Diamond Deck w/2" Skirt
Turntable Height:	3 5/8"
Turntable Drive:	3/4 hp DC Motor (Totally Enclosed Fan Cooled) Variable Speed Turntable 0-15 RPM with Soft Start and Soft Stop 4 Point Cam Follower Turntable Supports Easy Access Lubrication Points on Turntable Heavy-Duty #50 Roller Chain and Drive Sprocket Synthetic Lube in all Gearboxes (-30 - 120°F) Turntable Indexing Home Alignment
Controls:	Manual / Semi-Auto Switch Turntable Variable Speed Dial Dispenser Variable Speed Dial Film tension Variable Dial Film Carriage Up / Down Switch Emergency Stop Button 9 Diagnostic Lights for easy trouble shooting Photo Eye for Automatic Load Height Sensing Adjustable Top Wraps Adjustable Top of Load Over Wrap



Film Delivery:	Brake Motor Powered Stretch 8 setting Adjustable Variable Film Stretch (Brake Roller) Stretch Level 30% - 250% Force to Load Accepts 12" - 20" Rolls of Film on standard 3" Core
Film Carriage:	Film Carriage Top Delay and Auto-Stop Heavy Duty Enclosed Gear Drive 76" Wrap Height (Optional Wrap Height Available) Variable Speed Carriage 0-20 FPM 1/4 HP 90 Volt DC Motor 12 Point UHMW Carriage Guidance Supports Dispenser Kill Switch Top / Bottom
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Easy Access to all Components
Warranty:	3 year limited warranty (100% of all components).
Shipping Weight:	1,249 lb.

